



SAILUN

RETREAD SPECIFICATIONS

The specs listed below are a recommendation only. Buffing equipment can vary and, as such, the specs below should be verified or each different style of buffer. Buff profile should be verified using pilot skives of 3/32" across buffed tread surface.

SIZE	PATTERN	BUFFED CROWN RADIUS		BUFFED CROWN WIDTH		RIM WIDTH	
		mm	in	mm	in	in	
11R22.5	S605	660.0	26.0	220.0	8.66	8.25	
11R24.5		660.0	26.0	220.0	8.66	8.25	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5		711.0	28.0	220.0	8.66	8.25	
11R22.5	S606	660.0	26.0	220.0	8.66	8.25	
11R24.5		660.0	26.0	220.0	8.66	8.25	
12R22.5		610.0	24.0	230.0	9.06	8.25	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
295/80R22.5		660.0	26.0	220.0	8.66	9.00	
285/75R24.5		711.0	28.0	220.0	8.66	8.25	
315/80R22.5	S622	762.0	30.0	240.0	9.45	9.00	
11R22.5		660.0	26.0	210.0	8.27	8.25	
11R24.5		660.0	26.0	210.0	8.27	8.25	
255/70R22.5		711.0	28.0	200.0	7.87	7.50	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5		711.0	28.0	210.0	8.27	8.25	
215/75R17.5		S637	559.0	22.0	160.0	6.30	6.00
235/75R17.5			660.0	26.0	180.0	7.09	6.75
225/70R19.5			711.0	28.0	180.0	7.09	6.75
245/70R17.5			711.0	28.0	200.0	7.87	6.75
245/70R19.5	711.0		28.0	200.0	7.87	7.50	
265/70R19.5	610.0		24.0	200.0	7.87	7.50	
255/70R22.5	711.0		28.0	200.0	7.87	7.50	
275/70R22.5	762.0		30.0	230.0	9.06	7.50	
9R22.5	610.0		24.0	185.0	7.28	6.75	
10R22.5	610.0		24.0	200.0	7.87	7.50	
215/75R17.5	S737	508.0	20.0	155.0	6.10	6.00	
225/70R19.5		813.0	32.0	180.0	7.09	6.75	
245/70R19.5		711.0	28.0	200.0	7.87	7.50	
315/80R22.5		762.0	30.0	240.0	9.45	9.00	
12R22.5	S753	610.0	24.0	240.0	9.45	9.00	
10R22.5		610.0	24.0	200.0	7.87	7.50	
11R22.5		660.0	26.0	220.0	8.66	8.25	
11R24.5		610.0	24.0	220.0	8.66	8.25	
255/70R22.5		711.0	28.0	200.0	7.87	7.50	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5	S758	711.0	28.0	220.0	8.66	8.25	
11R22.5		660.0	26.0	220.0	8.66	8.25	
11R24.5	S768	610.0	24.0	220.0	8.66	8.25	
11R22.5		660.0	26.0	220.0	8.66	8.25	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5	S815	711.0	28.0	220.0	8.66	8.25	
11R22.5		660.0	26.0	220.0	8.66	8.25	
11R24.5		610.0	24.0	220.0	8.66	8.25	
11.00R20		660.0	26.0	220.0	8.66	8.00	
12R22.5		660.0	26.0	230.0	9.06	9.00	
255/70R22.5		711.0	28.0	200.0	7.87	7.50	
275/70R22.5		762.0	30.0	230.0	9.06	9.00	
315/80R22.5	S665	762.0	30.0	230.0	9.06	9.00	
11R22.5		660.0	26.0	220.0	8.66	8.25	
11R24.5		610.0	24.0	220.0	8.66	8.25	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5	SW01	711.0	28.0	220.0	8.66	8.25	
11R22.5		711.0	28.0	230.0	9.06	8.25	
11R24.5	S917	711.0	28.0	230.0	9.06	8.25	
11R22.5		660.0	26.0	220.0	8.66	8.25	
12R22.5		660.0	26.0	240.0	9.45	9.00	
11R24.5	S825	660.0	26.0	220.0	8.66	8.25	
12.00R24		711.0	28.0	240.0	9.45	8.50	
385/65R22.5		1067.0	42.0	310.0	12.20	11.75	
425/65R22.5		1067.0	42.0	330.0	12.99	12.25	
445/65R22.5	S740	1067.0	42.0	350.0	13.78	13.00	
225/70R19.5		813.0	32.0	190.0	7.48	6.75	
245/70R19.5	S811	711.0	28.0	200.0	7.87	7.50	
9.00R20		660.0	26.0	195.0	7.68	7.00	
10.00R20		610.0	24.0	220.0	8.66	7.50	
11.00R20		660.0	26.0	220.0	8.66	8.00	
12.00R20	S911	711.0	28.0	240.0	9.45	8.50	
10.00R20		610.0	24.0	210.0	8.27	7.50	
11.00R20	S698	660.0	26.0	230.0	9.06	8.00	
315/80R22.5		762.0	30.0	240.0	9.45	9.00	
11R22.5	S668	660.0	26.0	220.0	8.66	8.25	
11R24.5		660.0	26.0	220.0	8.66	8.25	
255/70R22.5		711.0	28.0	210.0	8.27	7.50	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
445/50R22.5	S696	2489.0	98.0	400.0	15.75	14.00	
11R22.5	S757	711.0	28.0	240.0	9.45	8.25	
11R24.5		711.0	28.0	240.0	9.45	8.25	
295/75R22.5		762.0	30.0	240.0	9.45	9.00	

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.

