



# TIRE LOAD LIMITS (lbs.) AT VARIOUS COLD INFLATION PRESSURES (kPA/psi)

TIRE SIZE	kPA		450	480	520	550	590	620	655	690	720	760	790	825	860	900									
	psi		65	70	75	80	85	90	95	100	105	110	115	120	125	130									
215/75R17.5	DUAL	lbs.		3305	3415	3525(E)	124	3640	3750	3860(F)	127	3970	4080	4190(G)	130	4300	4410	4540(H)	133						
	SINGLE	lbs.		3525	3640	3750(E)	126	3860	3970	4080(F)	129	4190	4300	4410(G)	132	4540	4675	4805(H)	135						
235/75R17.5	DUAL	lbs.		4190	4300	4410(E)	132	4510	4675	4805(F)	135	4940	5070	5205(G)	138	5355	5510	5675(H)	141						
	SINGLE	lbs.		4410	4510	4675(E)	134	4805	4940	5070(F)	137	5205	5355	5510(G)	140	5675	5840	6005(H)	143						
245/70R17.5	DUAL	lbs.		4190	4300	4410(E)	132	4510	4675	4805(F)	135	4940	5070	5205(G)	138	5355	5510	5675(H)	141						
	SINGLE	lbs.		4410	4510	4675(E)	134	4805	4940	5070(F)	137	5205	5355	5510(G)	140	5675	5840	6005(H)	143						
225/70R19.5	DUAL	lbs.	2600(D)	114	2720		2860	3000(E)	119	3115		3245	3415(F)	123	3490		3615	3750(G)	126	3855	3970(H)	128			
	SINGLE	lbs.	2755(D)	116	2895		3040	3195(E)	121	3315		3450	3640(F)	125	3715		3845	3970(G)	128	4100	4190(H)	130			
245/70R19.5	DUAL	lbs.	2910		3070		3220	3415		3515		3655	3860(F)	127	3940		4075	4300(G)	131	4345	4540(H)	133			
	SINGLE	lbs.	3085		3265		3425	3640		3740		3890	4080(F)	129	4190		4335	4540(G)	133	4620	4805(H)	135			
265/70R19.5	DUAL	lbs.	3195		3430		3600	3750		3930		4095	4300		4405		4415	4675(G)	134						
	SINGLE	lbs.	3415		3650		3830	3970		4180		4355	4540		4685		4850	5070(G)	137						
9.00R20	DUAL	lbs.		3860(D)	127	4045	4230		4410(E)	132	4585		4760	4940(F)	136	5080		5220	5355(G)	139	5515	5675(H)	141		
	SINGLE	lbs.		4080(D)	129	4280	4480		4675(E)	134	4850		5025	5205(F)	138	5360		5515	5675(G)	141	5840	6005(H)	143		
10.00R20	DUAL	lbs.		4380		4580	4760		4950		5205(F)	138	5415	5625		5840(G)	142	5895	5950		6005(H)	143	6310	6610(J)	146
	SINGLE	lbs.		4530		4770	4990		5220		5510(F)	140	5730	5950		6175(G)	144	6320	6465		6610(H)	146	6890	7160(J)	149
11.00R20	DUAL	lbs.		4780		4990	5190		5390		5675(F)	141	5785	5895		6005(G)	143	6265	6525		6780(H)	147			
	SINGLE	lbs.		4940		5200	5450		5690		6005(F)	143	6205	6405		6610(G)	146	6870	7130		7390(H)	150			
9R22.5	DUAL	lbs.		3270		3410	3550		3690		3860(E)	127	4005	4150		4300(F)	131	4425	4550		4675(G)	134			
	SINGLE	lbs.		3370		3560	3730		3890		4080(E)	129	4235	4390		4540(F)	133	4675	4810		4940(G)	136			
10R22.5	DUAL	lbs.		3860		4045	4230		4410(E)	132	4585		4760	4940(F)	136	5075		5210	5355(G)	139					
	SINGLE	lbs.		4080		4280	4480		4675(E)	134	4850		5025	5205(F)	138	5360		5515	5675(G)	141					
11R22.5	DUAL	lbs.		4380		4580	4760		4950		5205(F)	138	5415	5625		5840(G)	142	5895	5950		6005(H)	143			
	SINGLE	lbs.		4530		4770	4990		5220		5510(F)	140	5730	5950		6175(G)	144	6320	6465		6610(H)	146			
12R22.5	DUAL	lbs.		4780		4990	5190		5390		5675(F)	141	5785	5895		6005(G)	143	6265	6525		6780(H)	147			
	SINGLE	lbs.		4940		5200	5450		5690		6005(F)	143	6205	6405		6610(G)	146	6870	7130		7390(H)	150			
315/80R22.5	DUAL	lbs.		5345		5675	5840		6070		6395(G)	145	6545	6770		6940(H)	148	7210	7210		7610(J)	151	7910	8270(L)	154
	SINGLE	lbs.		5875		6175	6415		6670		6940(G)	148	7190	7440		7610(H)	151	7920	7920		8270(J)	154	8690	9090(L)	157
295/80R22.5	DUAL	lbs.		4860		5070	5305		5525		5840		5945	6150		6395		6550	6550		6780(H)	147	6950	7160(J)	149
	SINGLE	lbs.		5340		5510	5830		6070		6395		6535	6760		6940		7200	7200		7390(H)	150	7640	7830(J)	152
295/75R22.5	DUAL	lbs.		4095		4300	4540		4690		4885		5070(F)	137	5260		5440		5675(G)	141	5795	6005(H)	143		
	SINGLE	lbs.		4500		4725	4940		5155		5370		5510(F)	140	5780		5980		6175(G)	144	6370	6610(H)	146		
275/70R22.5	DUAL	lbs.				4805	4940		5070		5205		5355	5510		5675		5840	6005		6175		6395(H)	145	
	SINGLE	lbs.				5205	5355		5510		5675		5840	6005		6175		6395	6610		6780		6940(H)	148	
255/70R22.5	DUAL	lbs.	3415		3585		3765	3970		4110		4275	4410		4455		4610		4675(G)	134	4915	5070(H)	137		
	SINGLE	lbs.	3640		3815		4005	4190		4370		4550	4675		4895		5065		5205(G)	138	5400	5510(H)	140		
385/65R22.5	DUAL	lbs.																							
	SINGLE	lbs.	6060		6380		6720	6940		7350		7650	8050		8230		8510		8820		9050	9370(J)	158		9920(L)
425/65R22.5	DUAL	lbs.																							
	SINGLE	lbs.	7210		7590		7990	8270		8740		9100	9370		9790		10100		10500(J)	162	10700	11400(L)	165		
445/65R22.5	DUAL	lbs.																							
	SINGLE	lbs.	7800		8230		8660	9090		9480		9870	10200(H)	161	10600		11000		11400		11700	12300(L)	168		12800(M)
445/50R22.5	DUAL	lbs.																							
	SINGLE	lbs.	6175		6570		6940	7310		7680		8030	8390		8740		9090		9370(J)	158	9780	10200(L)	161		
12.00R24	DUAL	lbs.		6120		6390	6650		6910		7160		7390(G)	150	7610		7830		8050(H)	153	8300	8540(J)	155		
	SINGLE	lbs.		6330		6660	6980		7280		7580		8050(G)	153	8310		8570		8820(H)	156	9100	9370(J)	158		
11R24.5	DUAL	lbs.		4660		4870	5070		5260		5510(F)	140	5675	5840		6005(G)	143	6205	6405		6610(H)	146			
	SINGLE	lbs.		4820		5070	5310		5550		5840(F)	142	6095	6350		6610(G)	146	6790	6970		7160(H)	149			
285/75R24.5	DUAL	lbs.																							
	SINGLE	lbs.																							

\* Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.

