



S622 ^{EFT} FREE-ROLLING POSITION TRAILER

Code	Size	LI / SR	PR	T.D.	RIM	O.D.	S.W.	S.L.R.	Load Capacity		
									32nds	in.	in.
1001302	11R22.5	144/142 M	14	12	8.25	41.3	10.9	19.2	6175	5840	105
1001306	11R24.5	146/143 M	14	12	8.25	43.2	10.9	20.2	6610	6005	105
8245385 *	255/70R22.5	140/137 L	16	14	7.50	36.5	9.7	17.0	5510	5070	120
1001286	295/75R22.5	144/141 M	14	12	9.00	39.8	10.8	18.6	6175	5675	110
1001304	285/75R24.5	144/141 M	14	12	8.25	41.1	10.8	19.3	6175	5675	110

* Non-EFT Tire



The S622 EFT is a premium free-rolling position trailer tire. With a decoupling groove that resists irregular sidewall wear, and wide ribs to prevent damage caused by high-scrub applications, the S622 EFT is also a low-rolling resistance tire designed to maximize your mileage.

Features & Benefits

- Smartway Verified for lower rolling resistance and excellent fuel efficiency on highways.
- V-sipes improve traction in wet conditions and dissipate heat for prolonged tread life.
- Main groove stone ejectors protect tire against stone drilling.
- 5 full depth grooves for excellent traction in wet and dry conditions.
- Decoupling grooves help minimize irregular wear.



Applications:

- Free-Rolling Wheel Positions
- Trailers
- Tag Axles



SMARTWAY VERIFIED TIRE:
APPROVED FOR USE ON EPA SMARTWAY CERTIFIED EQUIPMENT



S622 EFT