



The Terramax RT (rugged terrain) is an aggressive, 3PMS certified RT tire. The Terramax RT features ample tread depth and provides excellent road manners for daily driving. Available in 36 sizes, from 17 to 22 inch rim diameters with flotation sizes available in 33,35 and 37 inches. The Terramax RT will enhance your vehicles appearance and no matter where you take it, on or off-road, the options are endless where you decide to go.




3 Peak Mountain Snowflake Certified (3PMS) for severe snow performance. LT sizes are also pinned for studs. 3D multi-wave siping adds traction on winter roads.



DEEP TREAD - THE REALITY
Deep tread depth, 16-18/32s. Tread extending out to sidewall create a desired appearance and provide real world function with extra traction and protection when the environment demands it.



Squared profile and staggered scalloped shoulder lugs with stone ejectors maximize traction while continuously removing debris in the voids. Center tread block design ensures vehicle stability. In addition, Finite Element Analysis promotes ride comfort with reduced road noise for a RT tire.



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	SINGLE MAX LOAD (LBS @ PSI)	DUAL MAX LOAD (LBS @ PSI)	SHIP WEIGHT (LBS)
1600135K	265/70R17	115T	SL	600/A/B	16	BSW	8.0	10.71	31.65	2679@44		42.5
1600137K	LT245/70R17	119/116Q	10PR		18	BSW	7.0	9.76	30.55	3000@80	2755@80	46.1
1600138K	LT245/75R17	121/118Q	10PR		18	BSW	7.0	9.76	31.73	3195@80	2910@80	47.3
1600139K	LT265/70R17	123/120Q	10PR		18	BSW	8.0	10.71	31.65	3415@80	3085@80	52.3
1600141K	LT285/70R17	126/123Q	10PR		18	BSW	8.5	11.50	32.76	3750@80	3415@80	56.7
1600144K	33X12.50R17LT	120Q	10PR		18	BSW	10.0	12.48	32.76	3085@65		60.8
1600145K	35X12.50R17LT	125Q	10PR		18	BSW	10.0	12.52	34.76	3640@80		65.2
1600146K	37X12.50R17LT	124Q	8PR		18	BSW	10.0	12.52	36.54	3525@80		67.3
1600143K	255/70R18	116T	XL	600/A/B	16	BSW	7.5	10.24	32.09	2756@50		43.4
1600147K	265/60R18	114S	XL	600/A/B	16	BSW	8.0	10.71	30.51	2601@50		41.3
1600190K	265/65R18	116T	XL	600/A/B	16	BSW	8.0	10.71	31.54	2756@50		43.4
1600149K	265/70R18	116S	SL	600/A/B	16	BSW	8.0	10.71	32.64	2756@44		41.3
1600150K	275/65R18	116T	XL	600/A/B	16	BSW	8.0	10.98	32.09	2756@50		44.3
1600151K	LT265/65R18	122/119Q	10PR		18	BSW	8.0	10.71	31.54	3305@80	3000@80	44.7
1600152K	LT265/70R18	124/121Q	10PR		18	BSW	8.0	10.71	32.64	3525@80	3195@80	41.9
1600153K	LT275/65R18	123/120Q	10PR		18	BSW	8.0	10.98	32.09	3415@80	3085@80	51.9
1600155K	LT275/70R18	125/122Q	10PR		18	BSW	8.0	10.98	33.19	3640@80	3305@80	53.8
5548704K	LT305/65R18	128/125 R	12PR		18	BSW	9.0	12.2	33.58	3970@80	3640@80	54.1
1600157K	33X12.50R18LT	122Q	12PR		18	BSW	10.0	12.52	32.76	3305@80		55.0
1600158K	35X12.50R18LT	128Q	12PR		18	BSW	10.0	12.52	34.76	3970@80		62.2
1600192K	37X12.50R18LT	128Q	10PR		18	BSW	10.0	12.52	36.54	3968@76		67.1
1600159K	265/50R20	111T	XL	600/A/B	16	BSW	8.5	10.91	30.47	2403@50		66.9
1600189K	275/55R20	117T	XL	600/A/B	16	BSW	8.5	11.18	31.89	2833@50		42.9
1600161K	275/60R20	116T	XL	600/A/B	16	BSW	8.0	10.98	32.99	2756@50		47.2
1600162K	LT275/55R20	120/117Q	10PR		18	BSW	8.5	11.18	31.89	3085@80	2835@80	48.4
1600164K	LT275/60R20	123/120Q	10PR		18	BSW	8.0	10.98	32.99	3415@80	3085@80	53.5
1600165K	LT275/65R20	126/123Q	10PR		18	BSW	8.0	10.98	34.09	3750@80	3415@80	55.7
1600398K	LT285/60R20	125/122 S	10PR		18	BSW	8.0	11.5	33.46	3640@80	3305@80	59.9
1600166K	LT305/55R20	125/122Q	12PR		18	BSW	9.5	12.44	33.23	3640@80	3305@80	63.2
1600167K	33X12.50R20LT	119Q	12PR		18	BSW	10.0	12.52	32.76	3000@80		62.7
1600168K	35X12.50R20LT	125Q	12PR		18	BSW	10.0	12.52	34.76	3640@80		66.3
1600194K	35X13.50R20LT	126Q	12PR		18	BSW	11.0	13.58	34.53	3750@80		71.1
1600169K	37X12.50R20LT	126Q	10PR		18	BSW	10.0	12.52	36.54	3750@80		70.7
1600170K	285/45R22	114Q	XL	600/A/B	16	BSW	9.5	11.22	32.09	2601@50		45.8
1600171K	33X12.50R22LT	114Q	12PR		18	BSW	10.0	12.52	32.52	2600@80		62.7
1600172K	35X12.50R22LT	121Q	12PR		18	BSW	10.0	12.52	34.53	3195@80		67.4
1600195K	37X12.50R22LT	127Q	12PR		18	BSW	10.0	12.52	36.54	3860@80		71.0
1600173K	37X13.50R22LT	128Q	12PR		18	BSW	11.0	13.6	36.5	3970@80		76.3