



The HLT C-Type is based on the proven Terramax HLT. Slight alteration to the existing HLT, that tightens the tread pattern to maximize weight carrying capabilities.

Engineered for commercial delivery and demanding regional applications. Enhanced casing and bead package.








REDUCED ROAD NOISE Tread pattern effectively reduces noise to create a quiet driving experience.

ENVIRONMENTALLY FRIENDLY PRODUCTION AND MATERIALS

Specially formulated compound for improved wear characteristics using the latest in environmentally friendly processes and materials.





LARGE CONTACT AREA Tread blocks increase the contact area, improving overall handling and tread wear.



WIDE CHANNEL GROOVES 4 extra-wide grooves channel water to give you the traction you need to drive with confidence.



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD Range	UTQG	TREAD DEPTH (32ND)	SIDE Wall	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	Single Max Load (LBS @ PSI)	DUAL MAX LOAD (LBS @ PSI)	Ship Weight (LBS)
5548248	185/60R15 C	94/92T	C	-	13	BSW	5.5	7.4	23.7	1477 @ 54	1389 @ 54	23
5548249	195/70R15 C	104/102R	D	-	13	BSW	6.0	7.9	25.8	1984 @ 65	1874 @ 6 5	25
5548250	205/65R15 C	102/100T	C	-	13	BSW	6.0	8.2	25.5	1874 @ 54	1764 @ 54	27
5548253	195/75R16 C	107/105R	D	-	13	BSW	5.5	7.7	27.5	2149 @ 69	2039 @ 69	28
5548252	215/55R16	97T XL	XL	500 A A	11	BSW	7.0	8.9	25.3	1609 @ 50	-	23
5548251	225/75R16 C	121/120R	E	-	13	BSW	6.0	8.8	29.3	3197 @ 83	3086 @ 83	34
5546501	235/65R16 C	121/119R	E		13	BSW	7.0	9.5	28.0	3197 @ 83	2998 @ 8 3	36