

TIRE LOAD LIMITS (KG/LBS.) AT VARIOUS COLD INFLATION PRESSURES (KPA/PSI)



TIRE SIZE		kPA psi	380	415	450	480	520	550	590	620	655	690	720	760	790	830	860	900
			55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130
215/75R17.5	DUAL	KG				1500	1550	1600(E) 124	1650	1700	1750(F) 127	1800	1850	1900(G) 130	1950	2050(H) 133		
	LB					3305	3415	3525(E) 124	3640	3750	3860(F) 127	3970	4080	4190(G) 130	4300	4540(H) 133		
	SINGLE	KG				1600	1650	1700(E) 126	1750	1800	1850(F) 129	1900	1950	2000(G) 132	2060	2180(H) 135		
	LB					3525	3640	3750(E) 126	3860	3970	4080(F) 129	4190	4300	4410(G) 132	4540	4805(H) 135		
235/75R17.5	DUAL	KG				1900	1950	2000(E) 132	2060	2120	2180(F) 135	2240	2300	2360(G) 138	2430	2500	2575(H) 141	
	LB					4190	4300	4410(E) 132	4510	4675	4805(F) 135	4940	5070	5205(G) 138	5355	5510	5675(H) 141	
	SINGLE	KG				2000	2060	2120(E) 134	2180	2240	2300(F) 137	2360	2430	2500(G) 140	2575	2650	2725(H) 143	
	LB					4410	4510	4675(E) 134	4805	4940	5070(F) 137	5205	5355	5510(G) 140	5675	5840	6005(H) 143	
245/70R17.5	DUAL	KG				1900	1950	2000(E) 132	2060	2120	2180(F) 135	2240	2300	2360(G) 138	2430	2500	2575(H) 141	
	LB					4190	4300	4410(E) 132	4510	4675	4805(F) 135	4940	5070	5205(G) 138	5355	5510	5675(H) 141	
	SINGLE	KG				2000	2060	2120(E) 134	2180	2240	2300(F) 137	2360	2430	2500(G) 140	2575	2650	2725(H) 143	
	LB					4410	4510	4675(E) 134	4805	4940	5070(F) 137	5205	5355	5510(G) 140	5675	5840	6005(H) 143	
225/70R19.5	DUAL	KG			1180(D) 114	1230	1300	1360(E) 119	1410	1470	1550(F) 123	1580	1640	1700(G) 126	1750	1800(H) 128		
	LB				2600(D) 114	2720	2860	3000(E) 119	3115	3245	3415(F) 123	3490	3615	3750(G) 126	3855	3970(H) 128		
	SINGLE	KG			1250(D) 116	1310	1380	1450(E) 121	1500	1570	1650(F) 125	1690	1740	1800(G) 128	1860	1900(H) 130		
	LB				2755(D) 116	2895	3040	3195(E) 121	3315	3450	3640(F) 125	3715	3845	3970(G) 128	4100	4190(H) 130		
245/70R19.5	DUAL	KG			1320	1390	1460	1550	1590	1660	1750(F) 127	1790	1850	1950(G) 131	1970	2060(H) 133		
	LB				2910	3070	3220	3415	3515	3655	3860(F) 127	3940	4075	4300(G) 131	4345	4540(H) 133		
	SINGLE	KG			1400	1480	1550	1650	1700	1770	1850(F) 129	1900	1970	2060(G) 133	2095	2180(H) 135		
	LB				3085	3265	3425	3640	3740	3890	4080(F) 129	4190	4335	4540(G) 133	4620	4805(H) 135		
265/70R19.5	DUAL	KG			1450	1560	1640	1700	1780	1860	1950	2000	2000	2120(G) 134				
	LB				3195	3430	3600	3750	3930	4095	4405	4405	4415	4675(G) 134				
	SINGLE	KG			1550	1660	1740	1800	1900	1970	2060	2130	2200	2300(G) 137				
	LB				3650	3950	4180	4350	4540	4850	5205	5205	5360	5707(G) 137				
9.00R20	DUAL	KG				1750(D) 127	1830	1910	2000(E) 132	2080	2160	2240(F) 136	2300	2360	2430(G) 139	2505	2575(H) 141	
	LB					3860(D) 127	4045	4230	4410(E) 132	4585	4760	4940(F) 136	5080	5220	5355(G) 139	5515	5675(H) 141	
	SINGLE	KG				1850(D) 129	1940	2030	2120(E) 134	2200	2280	2360(F) 138	2430	2500	2575(G) 141	2650	2725(H) 143	
	LB					4080(D) 129	4280	4480	4675(E) 134	4850	5025	5205(F) 138	5360	5515	5675(G) 141	5840	6005(H) 143	
10.00R20	DUAL	KG				1990	2080	2160	2250	2360(F) 138	2460	2560	2650(G) 142	2680	2710	2725(H) 143	2865	3000(J) 146
	LB					4380	4580	4760	4950	5205(F) 138	5415	5625	5840(G) 142	5895	5950	6005(H) 143	6310	6610(J) 146
	SINGLE	KG				2050	2160	2260	2370	2500(F) 140	2600	2700	2800(G) 144	2870	2940	3000(H) 146	3125	3250(J) 149
	LB					4530	4770	4990	5220	5510(F) 140	5730	5950	6175(G) 144	6320	6465	6610(H) 146	6890	7160(J) 149
11.00R20	DUAL	KG				2170	2260	2350	2440	2575(F) 141	2630	2680	2725(G) 143	2840	2960	3075(H) 147		
	LB					4780	4990	5190	5390	5675(F) 141	5785	5895	6005(G) 143	6265	6525	6780(H) 147		
	SINGLE	KG				2240	2360	2470	2580	2725(F) 143	2820	2910	3000(G) 146	3120	3240	3350(H) 150		
	LB					4940	5200	5450	5690	6005(F) 143	6205	6405	6610(G) 146	6870	7130	7390(H) 150		
9R22.5	DUAL	KG				1480	1550	1610	1670	1750(E) 127	1820	1890	1950(F) 131	2010	2070	2120(G) 134		
	LB					3270	3410	3550	3690	3860(E) 127	4005	4150	4300(F) 131	4425	4550	4675(G) 134		
	SINGLE	KG				1530	1610	1690	1760	1850(E) 129	1920	1990	2060(F) 133	2120	2180	2240(G) 136		
	LB					3370	3560	3730	3890	4080(E) 129	4235	4390	4540(F) 133	4675	4810	4940(G) 136		
10R22.5	DUAL	KG				1750	1830	1910	2000(E) 132	2080	2160	2240(F) 136	2300	2360	2430(G) 139			
	LB					3860	4045	4230	4410(E) 132	4585	4760	4940(F) 136	5075	5210	5355(G) 139			
	SINGLE	KG				1850	1940	2030	2120(E) 134	2200	2280	2360(F) 138	2430	2500	2575(G) 141			
	LB					4080	4280	4480	4675(E) 134	4850	5025	5205(F) 138	5360	5515	5675(G) 141			
11R22.5	DUAL	KG				1990	2080	2160	2250	2360(F) 138	2460	2560	2650(G) 142	2680	2710	2725(H) 143		
	LB					4380	4580	4760	4950	5205(F) 138	5415	5625	5840(G) 142	5895	5950	6005(H) 143		
	SINGLE	KG				2050	2160	2260	2370	2500(F) 140	2600	2700	2800(G) 144	2870	2940	3000(H) 146		
	LB					4530	4770	4990	5220	5510(F) 140	5730	5950	6175(G) 144	6320	6465	6610(H) 146		
12R22.5	DUAL	KG				2170	2260	2350	2440	2575(F) 141	2630	2680	2725(G) 143	2840	2960	3075(H) 147		
	LB					4780	4990	5190	5390	5675(F) 141	5785	5895	6005(G) 143	6265	6525	6780(H) 147		
	SINGLE	KG				2240	2360	2470	2580	2725(F) 143	2820	2910	3000(G) 146	3120	3240	3350(H) 150		
	LB					4940	5200	5450	5690	6005(F) 143	6205	6405	6610(G) 146	6870	7130	7390(H) 150		
315/80R22.5	DUAL	KG				2420	2575	2650	2750	2900(G) 145	2970	3070	3150(H) 148	3270	3450(J) 151	3590	3750(L) 154	
	LB					5345	5675	5840	6070	6395(G) 145	6545	6770	6940(H) 148	7210	7610(J) 151	7910	8270(L) 154	
	SINGLE	KG				2660	2800	2910	3030	3150(G) 148	3260	3370	3450(H) 151	3590	3750(J) 154	3940	4125(L) 157	
	LB					5875	6175	6415	6670	6940(G) 148	7190	7440	7610(H) 151	7920	8270(J) 154	8690	9090(L) 157	
305/70R22.5	DUAL	KG				2230	2360	2440	2540	2650	2730	2830	3000(H) 146	3010	3150(J) 148	3250	3350(L) 150	
	LB					4925	5205	5375	5595	5840	6025	6235	6610(H) 146	6640	6940(J) 148	7160	7390(L) 150	
	SINGLE	KG				2450	2575	2680	2790	2900	3000	3110	3250(H) 149	3310	3450(J) 151	3550	3650(L) 153	
	LB					5410	5675	5905	6150	6395	6620	6850	7160(H) 149	7300	7610(J) 151	7830	8050(L) 153	
295/80R22.5	DUAL	KG				2100	2200	2300	2400	2500	2650	2690	2790	2900	2980	3075(H) 147	3150	3250(J) 149
	LB					4630	4860	5070	5305	5525	5840	5945	6150	6395	6550	6780(H) 147	6950	7160(J) 149
	SINGLE	KG				2310	2420	2500	2640	2750	2900	2960	3070	3150	3270	3350(H) 150	3460	3550(J) 152
	LB					5090	5340	5510	5830	6070	6395	6535	6760	6940	7200	7390(H) 150	7640	7830(J) 152
295/75R22.5	DUAL	KG				1860	1950	2060	2130	2220	2300(F) 137	2390	2470	2575(G) 141	2630	2725(H) 143		
	LB					4095	4300	4540	4690	4885	5070(F) 137	5260	5440	5675(G) 141	5795	6005(H) 143		
	SINGLE	KG				2040	2140	2240	2340	2440	2500(F) 140	2620	2710	2800(G) 144	2890	3000(H) 146		
	LB					4500	4725	4940	5155	5370	5510(F) 140	5780	5980	6175(G) 144	6370	6610(H) 146		
275/70R22.5	DUAL	KG				2180	2240	2300	2360	2430	2500	2500	2500	2575	2650	2725	2800	2900(J) 145
	LB					4805	4940	5070	5205	5355	5510	5510	5510	5675	5840	6005	6175	6395(J) 145
	SINGLE	KG				2360	2430	2500	2575	2650	2725	27						